

High Definition Plasma Display

TH-42PF11EK

Product summary



- 42" 1080p High Definition Plasma Display for professional use.
- Equipped with three interchangeable slots-provide flexible and powerful system solution by adding/exchanging wide variety of optional slot-in boards.
- Available with various unique professional features-Weekly Command Timer, Dual picture mode, Digital zoom, Built-in video wall image enlarger, etc..
- Various Energy-saving functions-DPMS, Auto power off, Power save mode, etc..


Note: Dual picture mode cannot handle the following combinations of two analog signals Component - Component, Component - PC(RGB), PC(RGB) - Component, PC(RGB) - PC(RGB)

Product specification (Design and specifications subject to change without notice)


DISPLAY		
Screen Size (Diagonal)	42-inch (106 cm)	
Aspect ratio	16:9	
Effective Display Area (W x H)	922 x 518 mm	
Resolution (H x V)	1,920 x 1080 pixels (1pixel=3cells for R, G and B)	
Pixel Pitch (H x V)	0.480 x 0.480 mm	
Brightness	1,200 cd/m ²	
Contrast Ratio (Bright room)	30,000:1 (400:1)	
Dynamic contrast	1,000,000:1	
Gradation	5,120 steps (equivalent)	
APPLICABLE SIGNALS		
Scanning format	525(480)/60i•60p, 625(575)/50i•50p, 625(576)/50p, 750(720)/60p•50p, 1125(1080)/60i•60p•50i•50p•24p•25p•30p•24sF, 1250(1080)/50i	
PC Signal Compatibility	VGA, SVGA, XGA, WXGA, SXGA, SXGA*, UXGA (UXGA : compressed) Horizontal scanning frequency 15-110 kHz Vertical scanning frequency 48 -120 Hz	
INPUT / OUTPUT		
Fixed Terminal		
PC IN	Mini D-sub 15pin x 1 (Female) Analog RGB/Components *Plug & Play (VESA DDC 2B)	
AUDIO IN (L/R)	M3 jack x 1	
SERIAL	D-sub 9-pin x 1 (Male) External control, RS-232C compatible	
Interchangeable Terminals		
(Slot1) Vacant		
(Slot2) DVI-D IN	DVI x 1	
AUDIO IN(L/R)	M3 jack x 1	
(Slot3) COMPONENT IN	BNC x 3 Analog RGB/Components	
AUDIO IN (L/R)	RCA pin jack x 2	
ELECTRICAL		
Power Requirements	220 - 240 V AC, 50 Hz/60 Hz	
Power Consumption	410 W	
Power off condition	0.4 W	
Stand-by condition	Save OFF 1.2 W, Save ON 0.7 W	
SOUND		
Audio Output	16 W [8 W + 8 W] (10% THD)	
MECHANICAL		
Dimensions (W x H x D)	1,020 x 610 x 89 mm (99 mm when including protruding portion of slots)	
Weight	approx. 29.0 Kg/with speakers 33.0 Kg	
Cabinet Colour	Black	
ENVIRONMENTAL		
Operating environment		
Temperature	0 °C - 40 °C	
Humidity	20 % - 80 % (Non condensation)	
Altitude	0 - 2,800 m	
Storage environment		
Temperature	-20 °C - 60 °C	
Humidity	20 % - 90 % (Non condensation)	
Altitude	0 - 3,300 m	
RADIATION REGULATIONS		
EN55022 Class-B, EN55024, EN61000-3-2, EN61000-3-3		
SAFETY STANDARDS		
EN60065 Ver.7		
IR REMOTE CONTROL		
Power Requirements	DC 3V (2 x R6 (UM3) Size Batteries)	
Operation distance	approx. 7m in front of plasma display	
Weight	approx. 130g including batteries	
INCLUDED ACCESSORIES		
• Fixing Band • AC power cord x 2 • Operating instruction book • Remote control • Batteries		
OPTIONAL ACCESSORIES		
• Wall-hanging bracket (vertical,angled,drawer type) • Pedestal • Ceiling-hanging bracket • Mobile stand • Touch Panel • Speakers • Anti-Glare Filter • Terminal boards		

■ **Dimensions** (Shown with optional Pedestal stand)


Units : mm



<Terminal dimension>



<Connection terminals>



Preset Input Signals

Signal name	horizontal frequency (kHz)	vertical frequency (Hz)	Optional Terminal Board														
			Composite/Component Video TY-42TM6Y	Component Video TY-42TM6A/Z	PC Input TY-42TM6P	RGB Active Through TY-42TM6G	Composite Video TY-42TM6B/V	BNC Dual Video TY-FB9BD	DVI-D TY-FB11DD	SDI TY-FB7SD	HD-SDI TY-FB9HD	HD-SDI with Audio TY-FB10HD	Dual HD-SDI TY-FB11DHD	HDMI TY-FB8HM	Dual HDMI TY-FB10HMD	SCART TY-FB8SC	PC IN(D-sub 15-pin) Fixed Terminal
Composite	NTSC	15.73	59.94	Y												Y	
	PAL	15.63	50.00	Y												Y	
	PAL60	15.73	59.94	Y												Y	
	SECAM	15.63	50.00	Y												Y	
	Modified NTSC	15.73	59.94	Y												Y	
Component / RGB	525(480)/60i	15.73	59.94	Y	Y	Y	Y			Y	Y	Y					Y
	525(480)/60p	31.47	59.94	Y	Y	Y	Y		Y					Y	Y		Y
	625(575)/50i	15.63	50.00	Y	Y	Y	Y		Y	Y	Y						Y
	625(575)/50p	31.25	50.00	Y	Y	Y	Y										Y
	625(576)/50p	31.25	50.00						Y					Y	Y		
	750(720)/60p	45.00	60.00	Y	Y	Y	Y			Y	Y	Y		Y	Y		Y
	750(720)/50p	37.50	50.00	Y	Y	Y	Y		Y	Y	Y	Y		Y	Y		Y
	1125(1080)/60i	33.75	60.00	Y	Y	Y	Y		Y	Y	Y	Y		Y	Y		Y
	1125(1080)/60p	67.50	60.00	Y	Y	Y	Y		Y			Y		Y	Y		Y
	1125(1080)/50i	28.13	50.00	Y	Y	Y	Y		Y	Y	Y	Y		Y	Y		Y
	1125(1080)/50p	56.25	50.00	Y	Y	Y	Y		Y		Y	Y		Y	Y		Y
	1125(1080)/30p	33.75	30.00	Y	Y	Y	Y		Y	Y	Y	Y					Y
	1125(1080)/25p	28.13	25.00	Y	Y	Y	Y		Y	Y	Y	Y					Y
	1125(1080)/24p	27.00	24.00	Y	Y	Y	Y		Y	Y	Y	Y		Y			Y
	1125(1080)/24sF	27.00	48.00	Y	Y	Y	Y			Y	Y	Y					Y
	1250(1080)/50i	31.25	50.00	Y	Y	Y	Y										Y
	2048(1080)/24p	27.00	24.00											Y			
	2048(1080)/24sF	27.00	48.00											Y			
RGB	640×400@70Hz	31.46	70.07	Y	Y	Y	Y										Y
	640×480@60Hz	31.47	59.94	Y	Y	Y	Y		Y					Y	Y		Y
	640×480@72Hz	37.86	72.81	Y	Y	Y	Y										Y
	640×480@75Hz	37.50	75.00	Y	Y	Y	Y										Y
	640×480@85Hz	43.27	85.01	Y	Y	Y	Y										Y
	800×600@56Hz	35.16	56.25	Y	Y	Y	Y										Y
	800×600@60Hz	37.88	60.32	Y	Y	Y	Y		Y								Y
	800×600@72Hz	48.08	72.19	Y	Y	Y	Y										Y
	800×600@75Hz	46.88	75.00	Y	Y	Y	Y										Y
	800×600@85Hz	53.67	85.06	Y	Y	Y	Y										Y
	852×480@60Hz	31.47	59.94	Y	Y	Y	Y		Y								Y
	1024×768@50Hz	39.55	50.00						Y								
	1024×768@60Hz	48.36	60.00	Y	Y	Y	Y		Y								Y
	1024×768@70Hz	56.48	70.07	Y	Y	Y	Y										Y
	1024×768@75Hz	60.02	75.03	Y	Y	Y	Y										Y
	1024×768@85Hz	68.68	85.00	Y	Y	Y	Y										Y
	1066×600@60Hz	37.64	59.94	Y	Y	Y	Y		Y								Y
	1152×864@60Hz	53.70	60.00						Y								
	1152×864@75Hz	67.50	75.00	Y	Y	Y	Y										Y
	1280×768@60Hz	47.70	60.00	Y	Y	Y	Y										Y
	1280×960@60Hz	60.00	60.00	Y	Y	Y	Y										Y
	1280×960@85Hz	85.94	85.00	Y	Y	Y	Y										Y
	1280×1024@60Hz	63.98	60.02	Y	Y	Y	Y		Y								Y
	1280×1024@75Hz	79.98	75.03	Y	Y	Y	Y										Y
	1280×1024@85Hz	91.15	85.02	Y	Y	Y	Y										Y
	1366×768@50Hz	39.55	50.00						Y								
	1366×768@60Hz	48.36	60.00	Y	Y	Y	Y		Y								Y
	1400×1050@60Hz	65.22	60.00						Y								
	1600×1200@60Hz	75.00	60.00	Y	Y	Y	Y		Y								Y
	1600×1200@65Hz	81.25	65.00	Y	Y	Y	Y										Y
	1920×1080@60Hz	67.50	60.00	Y	Y	Y	Y										Y
	1920×1200@60Hz	74.04	59.95						Y								
	Mac13" (640×480)	35.00	66.67	Y	Y	Y	Y										Y
	Mac16" (832×624)	49.72	74.54	Y	Y	Y	Y										Y
	Mac21" (1152×870)	68.68	75.06	Y	Y	Y	Y										Y

Serial RS232C : D-sub 9-Pin (Male)



Pin Assignment and Signal Name

Pin No.	Signal name	Descriptions
1	CD	NC
2	RXD	Receive Data
3	TXD	Transmit Data
4	DTR	Not used
5	GND	Ground
6	DSR	Not used
7	RTS	Short Circuit
8	CTS	
9	RI	NC

Transmitting Conditions

Signal Level	Complied with RS232C
Synchronization method	Asynchronous
Baud Rate	9600 bps
Parity	None
Character Length	8 bits
Stop Bit	1 bit
Flow control	-

PC Input : D-Sub 15-Pin (Female)



Signal Name

Pin No.	Signal name
1	R (P _R /C _R)
2	G (Y)
3	B (P _B /C _B)
4	NC (Not connected)
5	GND (Ground)
6	GND (Ground)
7	GND (Ground)
8	GND (Ground)
9	+5V DC
10	GND (Ground)
11	NC (Not connected)
12	SDA
13	HD/SYNC
14	VD
15	SCL